

ตารางแสดงมาตรฐานของฟุกตะปู Ultra

Ultra Hammer Drive Anchor Specification Table

L.S.T. GROUP

A - 04



Hammer Drive Anchor Bolt

Contact Us

L.S.T. Supply
Tel: 0-2712-1112
Fax: 0-2712-3626
E-mail:
lstsupply@gmail.com

Soon Thai Jun Import
Tel: 0-2234-9555-8
Fax: 0-2639-4007
E-mail:
soonthaijun@gmail.com

Website:
www.groupilst.com

Size	Drill Hole Dia.	Drill Depth	Pull Out Load	Shear Load
M6-1.0 X 45	6.4 mm.	30 mm.	475 Kgs.	652 Kgs.
M6-1.0 X 60	6.4 mm.	30 mm.	475 Kgs.	652 Kgs.
M8-1.25 X 50	8.5 mm.	35 mm.	705 Kgs.	1,030 Kgs.
M8-1.25 X 70	8.5 mm.	35 mm.	705 Kgs.	1,030 Kgs.
M10-1.5 X 50	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M10-1.5 X 60	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M10-1.5 X 80	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M10-1.5 X 90	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M10-1.5 X 100	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M10-1.5 X 120	10.5 mm.	40 mm.	1,180 Kgs.	1,640 Kgs.
M12-1.75 X 60	12.7 mm.	45 mm.	1,826 Kgs.	2,380 Kgs.
M12-1.75 X 70	12.7 mm.	45 mm.	1,826 Kgs.	2,380 Kgs.
M12-1.75 X 90	12.7 mm.	45 mm.	1,826 Kgs.	2,380 Kgs.
M12-1.75 X 100	12.7 mm.	45 mm.	1,826 Kgs.	2,380 Kgs.
M12-1.75 X 120	12.7 mm.	45 mm.	1,826 Kgs.	2,380 Kgs.
M16-2.0 X 100	17 mm.	60 mm.	3,215 Kgs.	4,890 Kgs.
M16-2.0 X 120	17 mm.	60 mm.	3,215 Kgs.	4,890 Kgs.
M16-2.0 X 150	17 mm.	60 mm.	3,215 Kgs.	4,890 Kgs.
M20-2.5 X 130	21.5 mm.	80 mm.	4,450 Kgs.	7,510 Kgs.
M20-2.5 X 150	21.5 mm.	80 mm.	4,450 Kgs.	7,510 Kgs.
M20-2.5 X 190	21.5 mm.	80 mm.	4,450 Kgs.	7,510 Kgs.